

5 James Street * S. Hackensack • New Jersey 07458 Tel: 201-818-1616 • Fax: 201-818-8775 E-mail: <u>nofire@nofire.net</u> • Web Site: <u>http://www.nofire.com</u>

January 2011

Exciting news about NoFire's **S Barrier** Wrap System.

- A new instruction manual demonstrates the ease of S Barrier installation in a simple step by step procedure.
- **<u>NEW</u>** ... low, low prices. (available upon request)

As you are aware, S Barrier is a fully Underwriter's Laboratories (UL) 2-hour approved fire protection system for structural steel. S Barrier has many advantages as compared to other types of structural steel fire protection, including cementitious (spray type or trowel type), spray-on intumescent, concrete, and gypsum.

S Barrier's advantages include:

- 1. No steel preparation or steel priming required
- 2. No heating of steel (in winter) required
- 3. No evacuation of the work area required during application
- 4. No hazardous materials, no odors, no toxic gases during application
- 5. Less expensive than spray applied materials
- 6. No delamination or unhealthy fibers or vapors emitted over time
- 7. Can be used in clean rooms and hospitals
- 8. Impact resistant
- 9. No decay in performance over time
- **10.** Optional topcoating for exterior applications
- **11.** Available for 1, 2, 3, and 4 hour applications

FOR MORE INFORMATION CONTACT NoFire Technologies, Inc.